PATENT ABSTRACTS OF JAPAN

(11)Publication number:

62-250073

(43) Date of publication of application: 30.10.1987

(51)Int.CI.

CO9C 1/56

(21)Application number : 61-093661

(71)Applicant : ASAHI CARBON KK

(22)Date of filing:

23.04.1986

(72)Inventor: INOUE YASUMOTO

ASAZUMA TAKAHARU

(54) CARBON BLACK HAVING MODIFIED SURFACE AND PRODUCTION THEREOF (57)Abstract:

PURPOSE: To obtain the titled carbon black useful for rubber reinforcing and as a filler, having improved dispersibility and processing properties, by blending carbon black having large surface area with a solution of a p-phenylenediamine compound, etc., and drying at a specific temperature.

CONSTITUTION: (A) 100pts.wt. carbon black having ≥ 130m2/g specific surface area by nitrogen adsorption is blended with (B) an organic solvent (e.g. toluene, etc.) or water dispersion containing 0.5W50pts.wt. one or more compounds [e.g. N-(1-methylhepthyl)-N'-phenyl-pphenylenediamine, etc.] shown by formula I (R is isopropyl, 1,3-dimethylbutyl, 1-methylheptyl, phenyl, group shown by formula II or p-toluenesulfonyl), the solvent or water is removed and dried at 150W200°C to give the aimed compound wherein

the component B is added to the surface of the component A.

e

e

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

 \mathbf{g}

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office